



BIPRO

TM3G48M **96-cell**

435 - 455 W

16BB N



产品特性

体系及产品认证

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015
- ISO 14001: 2015
- ISO 45001: 2018



质量保证

保证功率

www.talesun.com

marketing.hq@talesun.com

| | STC | NMOT | STC | NMOT | STC | NMOT | STC | NMOT | STC | NMOT |
|--|-------|------|-------|------|-------|------|-------|------|-------|------|
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | 21.80 | | 22.00 | | 22.30 | | 22.50 | | 22.80 | |

| | 5% | 10% | 15% | 20% | 25% |
|--|-------|-------|-------|-------|-------|
| | 467 | 490 | 512 | 534 | 556 |
| | 29.79 | 29.79 | 29.79 | 29.79 | 29.79 |
| | 15.69 | 16.43 | 17.18 | 17.93 | 18.68 |
| | 35.42 | 35.42 | 35.42 | 35.42 | 35.42 |
| | 16.62 | 17.41 | 18.20 | 19.00 | 19.79 |

| | | |
|--|--|------|
| | N | 16BB |
| | 96 (6*16) | |
| | 1762*1134*30mm (69.37*44.65*1.18) | |
| | 24.7kg (54.45lbs) | |
| | | |
| | | |
| | IP68, 3 | |
| | 4mm ² (IEC), 12AWG(UL) 350mm(+),250mm(-) | |
| | T01/LJQ-3-CSY/MC4/MC4-EV02 | |